

# Heyco® Liquid Tight Fittings Torque Chart

Thread Size	Fitting (Description)	Heyco Part Numbers	Sealing Nut Torque	Locknut Torque
PG 7	RLTF 7	3444, 3445	25 in. lbs.	35 in. lbs.
	LTF 7	3207, 3208		
	Flex RLTF 7	3464, 3465		
	Flex LTF 7	3237, 3238		
PG 9	RLTF 9	3446, 3447	40 in. lbs.	40 in. lbs.
	LTF 9	3210, 3211		
	Flex RLTF 9	3466, 3467		
	Flex LTF 9	3240, 3241		
PG 11	RLTF 11	3448, 3449	65 in. lbs.	45 in. lbs.
	LTF 11	3213, 3214		
	Flex RLTF 11	3468, 3469		
	Flex LTF 11	3243, 3244		
PG 13.5*	LTF 13.5	3216, 3217	80 in. lbs.	80 in. lbs.
	Flex LTF 13.5	3246, 3247		
PG 16	LTF 16	3219, 3220	120 in. lbs.	124 in. lbs.
	Flex LTF 16	3249, 3250		
PG 21	RLTF 21	3454, 3455	130 in. lbs.	169 in. lbs.
	LTF 21	3222, 3223		
	Flex RLTF 21	3478, 3479		
	Flex LTF 21	3245, 3248		
PG 29	LTF 29	3225, 3226	275 in. lbs.	225 in. lbs.
3/8 NPT	RLTF 3/8	3458, 3459	40 in. lbs.	40 in. lbs.
	LTF 3/8	3228, 3229		
	Flex RLTF 3/8	3474, 3475		
	Flex LTF 3/8	3254, 3255		
1/2 NPT	LTF 1/2	3231, 3232	80 in. lbs.	80 in. lbs.
	Flex LTF 1/2	3251, 3252		
1/2 NPT	LLTF 1/2	3200, 3201	120 in. lbs.	124 in. lbs.
	Flex LLTF 1/2	3266, 3267		
3/4 NPT	RLTF 3/4	3460, 3461	130 in. lbs.	169 in. lbs.
	LTF 3/4	3234, 3235		
	Flex RLTF 3/4	3462, 3463		
	Flex LTF 3/4	3239, 3242		
1 NPT	RLTF 1	8439, 8440	225-250 in. lbs.	200-225 in. lbs.
	LTF 1	8437, 8438		

\*PG 13.5 is also known as PG 13.

Note: The values shown are for reference only. The torque value for sealing nuts may vary depending upon the crush resistance of the cable.

