more product protection

GRO Series



Grommets for Holes in Sheet Metal

GRO Series grommets provide mechanical protection for hoses, tubing, shafts, rods and cables as they pass through holes in sheet metal. Easily snapped into place, they are held securely by a molded bead until deliberately removed.

• UL approved for applications up to 221°F (105°C)

Material: FlexTemp (Thermoplastic Rubber) **Color:** Black



Grommets for Holes in Sheet Metal **GRO Series**

| Caplugs No. | Dimensions | | | | | | | | | | | | Packaging | |
|--------------|------------|-------|-----------------|------------|-----|------|------|-------|------|-------|------|-------|-----------|----------|
| | Hole Size | | Metal Thickness | | A | | В | | С | | D | | Carton | Mini Pak |
| | In | mm | In | mm | In | mm | In | mm | In | mm | In | mm | Quantity | Quantity |
| GRO-1/2-UL | .50 | 12.70 | .0308 | .76 - 2.03 | .28 | 7.11 | .81 | 20.57 | .54 | 13.72 | .41 | 10.41 | 5000 | 1000 |
| GRO-5/8-UL | .62 | 15.88 | .0308 | .76 - 2.03 | .31 | 7.87 | .93 | 23.62 | .66 | 16.76 | .52 | 13.21 | 5000 | 1000 |
| GRO-3/4-UL | .75 | 19.05 | .0308 | .76 - 2.03 | .35 | 8.89 | 1.06 | 26.93 | .79 | 20.07 | .65 | 16.51 | 5000 | 1000 |
| GR0-7/8-UL | .87 | 22.23 | .0308 | .76 - 2.03 | .35 | 8.89 | 1.19 | 30.22 | .91 | 23.11 | .77 | 19.55 | 5000 | 1000 |
| GRO-1-UL | 1.00 | 25.40 | .0308 | .76 - 2.03 | .35 | 8.89 | 1.32 | 33.53 | 1.04 | 26.42 | .89 | 22.61 | 5000 | 1000 |
| GR0-1-1/4-UL | 1.25 | 31.75 | .0308 | .76 - 2.03 | .35 | 8.89 | 1.60 | 40.64 | 1.29 | 32.77 | 1.12 | 28.45 | 2500 | 500 |