



Heyco® Cable Wrap

Standard Cut–Polyethylene (94V-0)

- Bundles and protects cables, wires, tubing, and hoses from 1/16" (1,6mm) to 2" (50,8mm) diameters.
- Absorbs vibration, insulates cables, and resists abrasion.
- Easy to use: twists on like tape!
- Allows breakouts of single/multiple wires and re-routing of replacement wires.
- Eight sizes available.
- Polyethylene and nylon material products are available in UV black or natural color.
- Conforms to the following Mil, Federal, and ASTM specifications:
 - Temp Range: 94V-0 76°C–101°C
 - Polyethylene Cable Wrap–UV Black and Natural
Fed. Spec LP390
Mil I-631D
Mil P-21922B
 - Temp Range: 94V-2, 85°C–93°C
 - Nylon Cable Wrap–UV Black
ASTM D4066 Group 2
Fed. Spec LP-410A
Mil T-47287A Type II
AS 1294
 - Nylon Cable Wrap–Natural
ASTM D4066 Group 2
Fed. Spec LP-410A
 - Standard Cut–Polyethylene (94V-0, 76°C–101°C)
 - Standard Cut–Nylon (94V-2, 85°C–93°C)
- Recognized under the component program of Underwriters' Laboratories File #E-173954.

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum Diameter		Maximum Diameter		UV Black	Natural		A Outside Diameter		B Pitch		C Thickness	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.062	1,6	.250	6,4	8900	8901	CW 125 PE	.125	3,2	.187	4,8	.032	0,8
.125	3,2	.375	9,5	8904	8905	CW 187 PE	.187	4,8	.250	6,3	.031	0,8
.187	4,8	.500	12,7	8908	8909	CW 250 PE	.250	6,3	.375	9,5	.045	1,1
.312	7,9	.750	19,1	8912	8913	CW 375 PE	.375	9,5	.438	11,1	.052	1,3
.375	9,5	1.000	25,4	8916	8917	CW 500 PE	.500	12,7	.500	12,7	.062	1,6
.500	12,7	1.250	31,8	8920	8921	CW 625 PE	.625	15,9	.625	15,9	.062	1,6
.750	19,1	1.500	38,1	8924	8925	CW 750 PE	.750	19,1	.750	19,1	.065	1,7
1.000	25,4	2.000	50,8	8928	8929	CW 1000 PE	1.000	25,4	1.000	25,4	.080	2,0

Standard Colors: UV Black or Natural.

Standard Cut–Nylon (94V-2)

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum Diameter		Maximum Diameter		UV Black	Natural		A Outside Diameter		B Pitch		C Thickness	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.062	1,6	.250	6,4	8932	8933	CW 125 N	.125	3,2	.187	4,8	.015	0,4
.125	3,2	.375	9,5	8936	8937	CW 187 N	.187	4,8	.250	6,3	.020	0,5
.187	4,8	.500	12,7	8940	8941	CW 250 N	.250	6,3	.375	9,5	.025	0,6
.312	7,9	.750	19,1	8944	8945	CW 375 N	.375	9,5	.438	11,1	.035	0,9
.375	9,5	1.000	25,4	8948	8949	CW 500 N	.500	12,7	.500	12,7	.035	0,9
.500	12,7	1.250	31,8	8952	8953	CW 625 N	.625	15,9	.625	15,9	.032	0,8
.750	19,1	1.500	38,1	8956	8957	CW 750 N	.750	19,0	.750	19,1	.032	0,8
1.000	25,4	2.000	50,8	8960	8961	CW 1000 N	1.000	25,4	1.000	25,4	.032	0,8

Standard Colors: UV Black or Natural.

