

"Stay Connected" with



HEYware Products

a PennEngineering® Company



- Ideal for securing, insulating, and routing cable and tubing.
- Cable and wire can be installed or removed for repair without removing clamp.
- Mounts with screws, mounting buttons or rivets.


Heyco® Nylon Wire Harness Clamps

MOUNTING HOLE DIAMETER	SCREW SIZE	PART DIMENSIONS						PART NO.			DESCRIPTION	STYLE		
		A Bundle Diameter		B Overall Length		C Width		Natural	Black	VO Natural				
in. mm.		in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.							
Snap Mouth *														
.157	4,0	#8	.50	12,7	1.18	30,0	.39	10,0	4127 4148	4127B 4148B	4127F 4148F	WHCX 500 WHCX 750	1	NEW!
			.71	18,0	1.38	35,1	.50	12,7						
Open Mouth														
.157	4,0	#8	.13	3,2	.77	19,5	.34	8,5	4149 4126	4149B 4126B	4149F 4126F	WHC 125 WHCX 250	2 3†	NEW!
			.25	6,4	.83	21,0	.39	10,0						
.205	5,2	#10	.25	6,4	.86	21,8	.41	10,4	4150 4152 4153 4154 4210 4211	4150B 4152B 4153B 4154B 4210B 4211B	4150F 4152F 4153F 4154F 4210F 4211F	WHC 250 WHC 375 WHC 500 WHC 625 WHC 750 WHC 1000 WHC 1500	3	
			.38	9,0	.83	21,0	.40	10,2						
			.50	12,5	1.16	29,4	.40	10,2						
			.63	15,9	1.13	28,6	.50	12,7						
			.75	19,1	1.28	32,5	.50	12,7						
			.95	25,1	1.50	38,1	.50	12,7						


Standard color natural.

*Bundle Diameter in closed position.


†No reinforcing ribs on Part No. 4126.



Style 1



Style 2



Style 3





- Retainer clip allows clamp to be pre-positioned on hose before final installation.
- Double row of teeth for more secure grip.
- Quick and easy installation. Tighten instantly with hand pliers or Air Tool (on page 7-39).
- Reusable. Can be removed without cutting.
- Supertough nylon clamps offer additional clamping strength.
- Outlast tubing under pressure.
- Non-conductive and non-magnetic.
- No moving pieces to seize or vibrate loose.
- Maximum Pressure Rating: 200 PSI.

Heyco® Nylon Locket™ Hose Clamps

EFFECTIVE CLAMP RANGE				PART NO.	DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter				A Clamp Thickness	B Strap Thickness		
in.	mm.	in.	mm.	Black	in.		mm.	in.	
LHC Series									
.34	8,7	.41	10,3	2388	LHC 344	.25	6,4	.08	2,0
.53	13,5	.59	15,1	2391	LHC 531				
.67	17,0	.81	20,6	2393	LHC 672				

Standard color black.



WHCX & WHC			LHC		
Material	Nylon 6/6	Nylon 6/6	Nylon 6/6 Supertough		
Flammability Rating	94V-2	94V-0	94HB		
Temperature Range	32°F (0°C) to 185°F (85°C)	-40°F (-04°C) to 185°F (85°C)	32°F (0°C) to 185°F (85°C)		