

a PennEngineering<sup>®</sup> Company




- Designed to easily mount to module or frame extrusions without the need for mounting holes or adhesives.
- Designed to be used with Heyco Stainless Steel Cable Ties up to .31" (8,0 mm) width or Heyco SunBundler Stainless Steel Wire Cable Ties.
- · Hold cable bundles parallel or perpendicular to the mounting frame.
- · Generous lead-in for installation without tools.
- Constructed from corrosion resistant 304 stainless steel.
- SunRunner CT-EZ designed for thicker module frames as well as racking systems - accommodates profiles up to .250" (6,4 mm) thick.
- UL Listed per UL 1565.


## HEYClip<sup>™</sup> SunRunner<sup>®</sup> CT Cable Tie Mounting Platforms

Stainless Steel Edge Clip

MAX CABLE TIE WIDTH		PANEL THICKNESS Clamping Range Minimum Maximum			INSERT POINTS	PART NO.	DESCRIPTION	FOOTPRINT A x B		REAR TAB LENGTH			
	in.	mm.	in.	mm.	in.	mm.				in.	mm.	in.	mm.
	SunRunner CT												
	.31	8,0	.06	1,5	.13	3,3	4	S6434	SunRunner CT 100 Pack	- 1.05 x .63	06 7 v 16 0	.77	19,5
								S6474	SunRunner CT Bulk		26,7 x 16,0		
	Su	nRunn	er CT-E	Z									
	.31	8,0	.13	3,3	.25	6,4	4	S6435	SunRunner CT-EZ 100 Pack	- 1.06 x .63	26,9 x 16,0	.77	19,5
								S6475	SunRunner CT-EZ Bulk				




Mount Parallel or Perpendicular



.11 (2,8 mm) TYPICAL PANEL THICKNESS

SunRunner<sup>®</sup> CT



SunRunner<sup>®</sup> CT-EZ

