

“Stay Connected” with



Strain Relief Bushings

a PennEngineering® Company

Heyco® Lockit™ ST and RDD Strain Relief Bushings

Table of UL Recognized Round Wire Types

Lockit™ Strain Reliefs for Round Cables										
Mounting Hole Diameter →	UL Approved for Cable Diameter Range			UL Approved for Cable Diameter Range and UL Type						
	11,5 x 13,0 mm	17,5 x 17,5 mm		.625" (15,9 mm) Ø	Will Fit Electrical Knock-outs .875" (22,2 mm) Ø			1.109" (28,2 mm) Ø		1.250" (31,8 mm) Ø
LOCKIT Lockit Variety	ST 101N	ST 201N	ST 301N	RDD 101 RDD 101-7 RDD 101-90	RDD 201 RDD 201-2 RDD 201-90	RDD 301 RDD 301-2 RDD 301-90	RDD 401 RDD 401-2	RDD 501	RDD 601	RDD 701
UL DIA. RANGE	.220" - .290"	.290" - .360"	.355" - .420"	.220" - .290" 5,6 - 7,4 mm	.290" - .385" 7,4 - 9,8 mm	.340" - .430" 8,6 - 10,9 mm	.420" - .450"	.525" - .600"	.600" - .700"	.720" - .830"
UL TYPE										
S	X	X	X	X	X	X	X	X	X	X
SE	X	X	X	X	X	X	X	X	X	X
SEO	X	X	X	X	X	X	X	X	X	X
SE00									X	
SE00W	X	X	X	X	X	X	X		X	X
SE0W	X	X	X	X	X	X	X		X	X
SJ	X	X	X	X	X	X	X	X	X	
SJE								X		
SJE00W	X	X	X	X	X	X	X			
SJE0W	X	X	X	X	X	X	X			
SJO	X	X	X	X	X	X	X	X	X	
SJ00	X	X	X	X	X	X	X	X	X	X
SJ00W	X	X	X	X	X	X	X			
SJ0W	X	X	X	X	X	X	X			
SJT								X	X	
SJTE00W	X	X	X	X	X	X	X			
SJTE0W	X	X	X	X	X	X	X			
SJTO	X	X	X	X	X	X	X	X		
SJT00	X	X	X	X	X	X	X	X		
SJT00W	X	X	X	X	X	X	X			
SJT0W	X	X	X	X	X	X	X			
SJTW	X	X	X	X	X	X	X			
SO	X	X	X	X	X	X	X	X	X	X
SO0	X	X	X	X	X	X	X	X	X	X
SO0W	X	X	X	X	X	X	X			X
SOW	X	X	X	X	X	X	X			X
SRDT									X	
ST									X	
ST0								X	X	
ST00								X	X	
ST00W									X	
ST0W									X	
SV	X	X	X	X	X	X	X			X
SVE	X	X	X	X	X	X	X			X
SVE0	X	X	X	X	X	X	X			X
SVE0	X	X	X	X	X	X	X			X
SVO	X	X	X	X	X	X	X			X
SVO0	X	X	X	X	X	X	X			X

Consult Heyco for UL Type designations not shown.